

Caterpillar

3508C - stage IIIA

Preliminary Technical Data

Document reference - EAME 101/2

Date - 11/06/2008

1000 kW

1800 rpm

Also consult:

Locomotive Engine Specification sheet:

Performance specification:

Engine arrangement:

This data is preliminary for information and commercially confidential. This form should not be circulated outside Caterpillar or the Caterpillar dealer network.

Engine specification			
1	UIC nominal engine power D-E or Fuel stop power D-H	1000	bkW
	Rated speed	1800	rpm
	Minimum low idle speed	600	rpm
	Engine torque	5307	Nm
	BMEP	1933	kPa
	BSFC at rated power and UIC conditions	209.2	g/kWh
	Optimum in performance map at UIC conditions	xx	g/kWh
	Number of cylinders / arrangement	8 / 60 V	
	Bore / stroke	170 / 190	mm
	Displacement per total	34.5	dm ³
	Engine dry weight	4795	kg
	Engine clearance length / height / width	2080 / 1953 / 1715	mm
	Engine flywheel housing number standard / option	OO / O	SAE
	Emissions regulation	Stage IIIA	

Air system			
2	Combustion air flow rate at UIC conditions	1.43	m ³ /sec
	Boost pressure	254	kPa,
	Intake manifold temperature	56	°C
	Max allowable airintake restriction w/ clean filter elements.	2.5	kPa
	Max allowable airintake restriction w/ dirty filter elements.	6.2	kPa

Control system			
3	Governor type	Electronic	

Engine jacket water and oilcooler cooling system - High temperature circuit			
4	Coolant capacity	88	dm ³
	Pump performance as function of radiator restriction	TM3097	
	Max allowable engine coolant outlet temperature	104	°C
	Regulator start to open / full open temperature	82 / 92	°C
	Regulator location	outlet	°C

Engine aftercooler cooling system - Low temperature circuit			
5	Coolant capacity	23	dm ³
	Pump performance min / max flow	300 / 430	l/min
	Max allowable coolant inlet temperature without engine derate	50	°C
	Regulator start to open / full open temperature	20 / 30	°C
	Regulator location	outlet	°C

Exhaust system			
6	Combustion air flow rate	3.36	m ³ /sec
	Exhaust stack temperature at rated (max at part load 495 °C).	409	°C
	Exhaust manifold temperature at rated (max at part load 700 °C)	631	°C
	Max allowable exhaust system back pressure	6.7	kPa
	Manifold type	Dry	

Fuel system			
7	Fuel system type	Electronic Unit Injector	
	Max. fuel flow to engine (to transfer pump)	21	l/min
	Max allowable fuel supply line restriction (incl. Primary fuel filter)	30	kPa
	Max allowable fuel temperature to engine	66	°C
	Max fuel flow from engine (return line)	20.7	l/min
	Max allowable fuel return line restriction.	27	kPa
	Fuel system pressure nominal	415	kPa

Lubrication system			
8	Recommended oil type (CAT spec)	CAT ECF-1 / API CG - 4	
	Lube oil consumption after 100 hrs average	0.17	g/kW.h
	Lube oil flow rate minimum	340	l/min
	Sump capacity standard / deep	228 / 466	dm ³
	Top-up capacity dip stick: min / max	xx / xx	dm ³
	Oil manifold pressure at rated speed max / min	448 / 379	kPa
	Oil manifold pressure at low idle speed min (warning)	155	kPa
	Oil manifold temperature nominal	97 - 100	°C

Engine heat rejection			
9	Heat rejection from engine and oil cooler HT	642	kW
	Heat rejection from aftercooler LT	108	kW
	Heat rejection from radiation	116	kW

Environment conditions			
10	Min cranking speed	120	rpm
	lowest ambient start temperature without assistance	10	°C
	maximum engine room temperature	70	°C